

In the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (Currently Amended) A pixel structure of transfective LCD disposed between a first data line and a second data line, comprising:

a reflective cell comprising a first transistor and a first reflective electrode, wherein the first transistor comprises a gate coupled to a scan line, a source coupled to the first data line, and a drain coupled to the first reflective electrode, and the first transistor is covered by the first reflective electrode;~~and~~

a transmission cell comprising a second transistor and a transparent electrode, wherein the second transistor comprises a gate coupled to the scan line, a source coupled to the second data line, and a drain coupled to the transparent electrode, and the second transistor is covered by a second reflective electrode;

a first storage capacitor coupled to the first transistor; and

a second storage capacitor coupled to the second transistor.

2. (Original) The pixel structure of transfective LCD of claim 1, wherein the second reflective electrode is a first reflective electrode of another pixel structure.

3. (Original) The pixel structure of transfective LCD of claim 1, wherein the drain of the first transistor is coupled to the first reflective electrode by a first plug, and the drain of the second transistor is coupled to the transmission electrode by a second plug.

4. (Currently Amended) The pixel structure of transfective LCD of claim 3, ~~further comprising a~~ wherein the first metal layer and a second storage capacitors are metal layers; ~~acting as storage capacitors,~~ disposed under the first plug and the second plug respectively.

5. (Currently Amended) A pixel structure of transfective LCD disposed between a first data line and a second data line, comprising:

a reflective cell comprising a first transistor and a first reflective electrode, wherein the first transistor comprises a gate coupled to a scan line, a source coupled to the first data line, and a drain coupled to the first electric electrode; and

a transmission cell comprising a second transistor and a transparent electrode, wherein the second transistor comprises a gate coupled to the second line, a source coupled to the second data line, and a drain coupled to the transparent electrode, and the first transistor and the second transistor are covered by the first reflective electrode; and

at least one storage capacitor coupled to the first and second transistors.

6. (Original) The pixel structure of transfective LCD of claim 5, wherein the drain of the first transistor is coupled to the first reflective electrode by a first plug, and the drain of the second transistor is coupled to the transparent by a second plug.

7. (Currently Amended) The pixel structure of transfective LCD of claim 6, ~~further comprising wherein the at least one storage capacitor comprises:~~

a first metal layer, disposed under the first plug, coupled to the first transistor via the first plug; and

a second metal layer, ~~acting as storage capacitors,~~ disposed under the ~~first plug and the~~ second plug ~~respectively,~~ coupled to the second transistor via the second plug.

8. (Original) The pixel structure of transfective LCD of claim 5, wherein the first data line and the second data line are bent, the drain of the first transistor is coupled to the first reflective electrode by a first plug, and the drain of the second transistor is coupled to the transparent by a second plug.

9. (Currently Amended) The pixel structure of transfective LCD of claim 8, ~~further comprising wherein the at least one storage capacitor is a metal line disposed under the drains of the first and second transistor, acting as a storage capacitor.~~

10. (Currently Amended) The pixel structure of transfective LCD of claim ~~8~~9, wherein the metal line is bent, ~~and the metal line acting as a storage capacitor is disposed under the drains of the first and second transistor.~~

11. (Currently Amended) A pixel structure of transfective LCD disposed between a first data line and a second data line, comprising:

a reflective cell comprising a first transistor and a first reflective electrode, wherein the first transistor comprises a gate coupled to a first scan line, a source coupled to the first data line, and a drain coupled to the first reflective electrode, and the first transistor is covered by the first reflective electrode; and

a transmission cell comprising a second transistor and a transparent electrode, wherein the second transistor comprises a gate coupled to a second scan line, a source coupled to the first data line, and a drain coupled to the transparent electrode, and the second transistor is covered by a second reflective electrode;

a first storage capacitor coupled to the first transistor; and

a second storage capacitor coupled to the second transistor.

12. (Original) The pixel structure of transfective LCD of claim 11, wherein the second reflective electrode is a first reflective electrode of another pixel structure.

13. (Original) The pixel structure of transfective LCD of claim 11, wherein the drain of the first transistor is coupled to the first reflective electrode by a first plug, and the drain of the second transistor is coupled to the transparent electrode by a second plug.

14. (Currently Amended) The pixel structure of transfective LCD of claim 13, ~~further comprising wherein the~~ a first metal layer and a second metal layer, acting as storage capacitors, are metal layers disposed under the first plug and the second plug respectively.

15. (Currently Amended) A pixel structure of transfective LCD disposed between a first data line and a second data line, comprising:

a reflective cell comprising a first transistor and a first reflective electrode, wherein the first transistor comprises a gate coupled to a scan line, a source coupled to the first data line, and a drain coupled to the first reflective electrode; and

a transmission cell comprising a second transistor and a transparent electrode, wherein the second transistor comprises a gate coupled to a second scan line, a source coupled to the first data line, and a drain coupled to the transparent electrode, and the first and second transistor are covered by the first reflective electrode; and

at least one storage capacitor coupled to the first and second transistors.

16. (Original) The pixel structure of transfective LCD of claim 15, wherein the drain of the first transistor is coupled to the first reflective electrode by a first plug, and the second transistor is coupled to the transparent electrode by a second plug.

17. (Currently Amended) The pixel structure of transfective LCD of claim 16, ~~further comprising wherein the~~ at least one storage capacitor comprises:

a first metal layer, disposed under the first plug, coupled to the drain of the first transistor via the first plug; and

a second metal layer, acting as storage capacitors, disposed under the first plug and the second plug respectively, coupled to the drain of the second transistor via the second plug.

18. (Original) The pixel structure of transflective LCD of claim 15, wherein the first transistor and the second transistor are disposed on different sides under the transparent electrode.

19. (Currently Amended) The pixel structure of transflective LCD of claim 16, ~~further comprising~~ wherein the at least one storage capacitor is a first metal layer acting as a storage capacitor disposed under the first plug, and extending to an underside of the drain of the second transistor.